SolarEdge Home Hot Water Controller

For Europe

SMRT-HOT-WTR-30-S2 / SMRT-HOT-WTR-50-S2

SMART ENERGY

Maximizes self-consumption by storing excess solar energy as hot water

- Integrates seamlessly with the complete SolarEdge Home ecosystem, offering a single source for warranty, support and training, to streamline logistics & operations
- Automatically adjusts power supplied to the heater, using any amount of available PV power (up to 5.0kW)
- Wireless communication to the inverter using SolarEdge Home Network, reducing wiring, labor, and installation faults
- Built-in water tank power consumption meter
- Simple wall mount installation
- Suitable for powering purely resistive loads only
- Optional temperature sensor for optimized heating

solaredge

SolarEdge Home Hot Water Controller

For Europe

SMRT-HOT-WTR-30-S2 / SMRT-HOT-WTR-50-S2

	SMRT-HOT-WTR-30-S2	SMRT-HOT-WTR-50-S2	
ELECTRICAL SERVICE			
Operating Voltage Range	205 – 264		Vac
AC Frequency	50		Hz
Nominal Voltage	230		Vac
Supported Grids	L / N / PE		
Maximum Supported Load Size	3.0	5.0	kW
Input Overvoltage Protection(1)	264		Vac
Maximum Load Current Rating	13	22	A
Minimum Output Power	5% of load rating		
Load Type	Resistive		
Efficiency	> 98		%
Output Overcurrent Protection	13	22	A
External Overcurrent Protective Device Rating	≥ 20	≥ 25	A
Type of Action	Type 1 C		
COMMUNICATION			
Supported Communication Protocol	SolarEdge Home Network		
Device Configuration	Monitoring platform/app or SetApp; Ethernet connection is required		
Operating Frequency Range	863 – 870 (EU)		MHz
Modulation	O-QPSK (Quadrature phase shift keying)		
EIRP with Antenna	14 (EU)		dBm
STANDARD COMPLIANCE			
Radio	ETSI EN 300 328 V 1.8.1, ETSI EN 301 489-1, ETSI EN 301 489-17		
Safety	IEC-60730-1		
Emissions	EN61000-6-1,2,3, EN61000-4-2,3,4,5,6,8,11, EMC directive 2014/30/EU		
INSTALLATION SPECIFICATIONS			
Dimensions (H x W x D)	375 x 240 x 110 / 14.7 x 9.5 x 4.5		mm / inch
Weight	5.3 / 11.7		kg / lb
Operating Temperature Range	-10 to +50 / +14 to +122		˚C / ˚F
Maximum Distance between Device and Load/Cable Cross-Section	3/10 for 15 AWG / 1.5mm^2 20/65 for 13 AWG / 2.5mm^2	3/10 for 13 AWG / 2.5mm^2 20/65 for 11 AWG / 4mm^2	AWG / mm^2
Terminal Block Minimum Wire Cross-Section	15 / 1.5		AWG / mm^2
Interfaces	1. AC in; 2. AC out; 3. External antenna RP SMA		
Cable Gland Diameters	2 glands 6-12, 1 gland 4-8		
Mounting Type	Wall mount		
IP Rating	IP65		
Self-Consumption	< 2.5		W
SENSOR SPECIFICATIONS(2)			
Sensor Type	Pt100 (100 Ohms @ 0°C) to IEC 751, Class B, ¾ wire		
Construction	6.0mm diameter stem in 316 stainless steel		
Termination	IP67 aluminum alloy weatherproof connection head with 4 wire connection block, M20 x 1.5mm cable entry (gland included)		
Process Connection	1/2" NPT parallel		
Probe Temperature Range	-100°C to +450°C (connection head @ 170°C)		
Probe Diameter	Ø6mm (¼")		
Probe Length	150mm ½" BSPP		
Temperature Accuracy	1		%

(1) The device stops diverting power to the load when this threshold is exceeded.
(2) Temperature sensor ordered separately. For more information, please contact SolarEdge.

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc.
All other trademarks mentioned herein are trademarks of their respective owners. Date: October 24, 2022 DS-000187-EU. Subject to change without notice.